



## MianKang Bearing Co., Ltd.



6002lu Bearing 2D drawings and 3D CAD models

15,000 mm x 32,000 mm x 9,000 mm ntn 6002lu bearing

Bearing No. 6002lu

Size	15x32x9 mm
Bore Diameter	15,000 mm
Outer Diameter	32,000 mm
Width	9,000 mm
d	15,000 mm
D	32,000 mm
B	9,000 mm
C	9,000 mm
rs min	0.3 mm
Radial clearance class	CN
Mass	0.03 kg
Dynamic load, C	5.6 kN
Static load, C0	2.83 kN
Fatigue limit load, Cu	0.13 kN
f0	13.9
Nlim (grease)	15,000 rpm
Min operating temperature, Tmin	-25 ° C
Max operating temperature, Tmax	110 ° C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.73 Hz
Characteristic outer ring frequency, BPF0	3.59 Hz
Characteristic inner ring	5.41 Hz



## MianKang Bearing Co., Ltd.

frequency, BPFI	
da min	17 mm
da max	19 mm
Da max	30 mm
ra max	0.3 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359318517
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	15MM Bore; 32MM Outside Diameter; 9MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; Co
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricated



## MianKang Bearing Co., Ltd.

Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Weight / LBS	0.0753
Outside Diameter	1.26 Inch   32 Millimeter
Bore	0.591 Inch   15 Millimeter
Outer Race Width	0.354 Inch   9 Millimeter
Inner Race Width	0 Inch   0 Millimeter