



MianKang Bearing Co., Ltd.

skf snl 528 bearing

Bearing No. snl 528

Category	Mounted Units & Inserts
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	42.438
EAN	7316570839074
Product Group	M06288
inside diameter:	140 mm, 125 mm, 5.0000 in, 4.9375 in
housing material:	Cast Iron
base to bore centerline:	150 mm
compatible bearing type:	Spherical Roller
overall length:	19.6875 in
finish/coating:	Uncoated
overall height:	11.9375 in
compatible bearing series/part number:	22228CC/W33, 22228CCK/W33, C2228 K, 23228CCK/W33, 23228CC/W33, C2228 22228CC/W33 22228CCK/W33 C2228 K 23228CCK/W33 23228CC/W33 C2228
overall width:	8.1250 in
bolt center-to-center length:	16-9/16 in
mounting:	Two-Bolt Base
base width:	5-15/16 in
housing construction:	Split Pillow Block
series:	SNL
compatible bore diameter:	140 mm, 125 mm, 5.0000 in,



MianKang Bearing Co., Ltd.

	4.9375 in
standards met:	ISO/DIS 185 Grade 200
Bearing (basic designation)	23228 K
Locating ring	2 x FRB 5/250
d_a	125.412 mm
C_a	98 mm
D_a	250 mm
D_b	177.5 mm
A	205 mm
A_1	150 mm
H	302 mm
H_1	150 mm
H_2	50 mm
J	420 mm
L	500 mm
N	42 mm
N_1	35 mm
J_6	458 mm
J_7	54 mm
N_4 max.	12 mm
A_{2L}	223 mm
P_{0°	1000 kN
P_{55°	1050 kN
P_{90°	630 kN
P_{120°	470 kN
P_{150°	430 kN
P_{180°	530 kN
P_a	345 kN
Q_{120°	900 kN
Q_{150°	520 kN
Q_{180°	450 kN
Mass housing	40 kg



MianKang Bearing Co., Ltd.

Cap bolt, size	M 24x130
Cap bolt, rec. tightening torque	350 N · m
Appropriate attachment bolt, size G	30 mm
Appropriate attachment bolt, rec. tightening torque	1310 N · m
Initial grease fill, 20%	900 g
Initial grease fill, 40%	1400 g
Bearing (basic designation)	22228 K
Locating ring	2 x FRB 15/250
d_a	125.412 mm
C_a	98 mm
D_a	250 mm
D_b	177.5 mm
A	205 mm
A_1	150 mm
H	302 mm
H_1	150 mm
H_2	50 mm
J	420 mm
L	500 mm
N	42 mm
N_1	35 mm
J_6	458 mm
J_7	54 mm
N_4 max.	12 mm
A_{2L}	223 mm
P_{0°	1000 kN
P_{55°	1050 kN
P_{90°	630 kN
P_{120°	470 kN
P_{150°	430 kN



MianKang Bearing Co., Ltd.

P_{180°	530 kN
P_a	345 kN
Q_{120°	900 kN
Bearing (basic designation)	23228 K
Locating ring	2 x FRB 5/250
d_a	127 mm
C_a	98 mm
D_a	250 mm
D_b	177.5 mm
A	205 mm
A_1	150 mm
H	302 mm
H_1	150 mm
H_2	50 mm
A_{2T}	285 mm
d_2	224 mm
d_b	155 mm